



www.nitrofillnow.com

1-877-2GO-FILL

E-135

Nitrogen Generator and Inflator

Need to Service Nitrogen Filled Tires but Don't Need a Costly Generator or the Hassles and On-Going Expenses of Cylinders?

The NEW NitroFill E-135 Generator/Inflator is specifically designed for locations that do not perform nitrogen conversions but need a solution to enable them to service nitrogen filled tires. While this high performance 3 cfm generator is capable of performing nitrogen conversions in light use applications, it is best used as a nitrogen "source," for quickly and easily calibrating nitrogen-filled tires.

The NitroFill E-135 is also a perfect fit for busy facilities desiring multiple "Top-Off" stations or a unit that can calibrate tires without tying up their main generator.

The E-135 converts your shop air into high purity (Up to 99.9%!) nitrogen providing you with an endless supply for top-offs and light conversions.

With its integrated automatic inflator, the E-135 provides instant, *dead*-accurate inflation by simply touching the air chuck to a tire valve stem. Use couldn't be easier, simply select the desired inflation value, connect the air chuck to the tire valve and wait for the *beep*. The E-135 automatically inflates or deflates any tire to the desired value in seconds.

Features:

- Complete System, nothing else to buy.*
- Integrated Automatic Inflator
- Advanced PSA nitrogen generation system.
- Instant and uninterrupted flow with guaranteed purity up to 99.9%.
- Each unit comes fully assembled, *just plug and play!*
- 5 year warranty* *

*Requires minimum 5 cfm, 150 psi compressor to power.

** See your NitroFill Distributor or visit www.nitrofillnow.com for details.

General Specifications

Power Requirement	100-240Vac 50/60Hz
Operating Temperature	-4°F to 158°F
Compressed Air Input Range	87-123psi (min 5 cfm)
Compressed Air Quality	0.01 ppm
Nitrogen Purity	95-99+%
Nitrogen Output	3.0cfm @ 116psi pressure
Maximum Nitrogen Pressure in Tank	102psi
Net Weight	156.5lbs
Gross Weight	194lbs
Dimensions (H*W*D)	49.6*17.7*23.2 inch
Packing Size (H*W*D)	54.3*20.1*28.7 inch

Inflator Specifications/Information

Self Calibrating
Self Diagnostic
Automatic Start
Back Lit LCD Display
Adjustable Over Pressure Setting
Accurate to +/- 0.5 PSI
Operating Range: 5-102 PSI

Note:

Includes 26 ft service hose and chuck.
Also available in 12 volt design.

