



www.nitrofillnow.com

1-877-2GO-FILL

E-170H

Nitrogen Generator

The NitroFill E-170H is our industry leading E-170 minus the automatic inflation unit, providing a high out-put [13.5 cfm] nitrogen generation system for applications that do not require an automated inflater.

Features:

- Complete System, nothing else to buy.
- Twin, exterior mounted high performance inlet air filters.
- Advanced PSA design.
- 5 year warranty*
- Instant and uninterrupted flow with guaranteed purity up to 99.9%.
- Each unit comes fully assembled, just plug and play!

*See your NitroFill Distributor or visit www.nitrofillnow.com for details.



General Specifications

Power Requirement	100-120Vac 50/60Hz
Operating Temperature	-4°F to 158°F
Compressed Air Input Range	100-200psi
Compressed Air Quality	0.01ppm
Nitrogen Purity	95-99+% (Adjustable)
Nitrogen Output	13.5 CFM rated at 160psi, 80°F.
Maximum Nitrogen Pressure in Tank	145-174psi
Shipping Weight	465 Pounds
Dimensions (Container)	57"H x 28.5"W x 26"D
Dimensions (Unit)	52"H x 28"W x 24"D

Options:

30 gallon Expansion Tank

Increases nitrogen output and reduces inflation times. Designed for facilities servicing a large percentage of Pick-Up Trucks, SUV's or other vehicles equipped with large, voluminous tires.



Caster Upgrade Kit

Adds stability and eases mobility by increasing caster diameter and unit "foot-print".



12 Volt Power Option

The E-170H is also available in a 12 Volt power configuration. Order an E-170H with this option and power it from any standard 12 Volt vehicle battery. Unit power cord is equipped with "Alligator Clips" to permit quick under-hood attachment to vehicle battery.