



# Chicago Pneumatic



## CP7748



- ✓ **Durable**
- ✓ **Powerful**
- ✓ **Economical**



**Maintenance** TOOLS

**People. Passion. Performance.**

# CP7748

## DURABLE & POWERFUL

### Powerful

922 ft-lbs. (1250 Nm)

Maximum removal torque

### EXTREME TORQUE

922 ft-lbs. (1250 Nm) - Maximum real torque in reverse

### RUGGED

Aluminum backed housing

### DURABLE

Twin hammer clutch

### MAXIMUM CONTROL

3 power settings

### FRICTION RING SOCKET RETAINER

Common retainer for 1/2" impacts

### INSULATION & COMFORT

Thermo-plastic rubber injected in housing for a durable and comfortable grip. Resistant to most chemicals used in workshops

### GREAT CONTROL

Full teasing trigger

### LIGHTWEIGHT

Composite housing

### QUIET

Decreases fatigue of the operator

### Applications:

- General maintenance on vehicles
- Tire changing on light vehicles
- Industrial maintenance and repair

Model Number	Part Number	Clutch Type	Socket Retainer	Square drive	Free Speed	Working Torque		Max Torque		Tool Weight		Tool Length		Avg. Air consumption		Air Cons. @ Load		Sound Pressure	Sound Power	Vibration
				in.		ft-lbs.	Nm	ft-lbs.	Nm	lbs	kg	in	mm	cfm	l/s	cfm	l/s			
<b>CP7748</b>	894 107 7480	Twin Hammer	Friction ring	1/2"	8200	75-580	102-786	922	1250	4,4	2	7,68	195	5,2	2,5	21	10	93	104	7,4 (2,2)
<b>CP7748-2</b>	894 107 7482	Twin Hammer	Friction ring	1/2"	8200	75-580	102-786	922	1250	4,9	2,25	9,68	245	5,2	2,5	21	10	93	104	7,4 (2,2)





## Over 110 years of experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications.

Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools and air compressors are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well. To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit [www.cp.com](http://www.cp.com).

## TUNE-UP & REPAIR KITS

MODEL	TUNE-UP KIT	REPAIR KIT
<b>CP7748</b>	894 016 9810	14 kits available see parts list



## DIMENSIONS

MODEL		<b>CP7748</b>	<b>CP7748-2</b>
A	in.	7.7	9.7
	mm	195	245
B	in.	7.4	7.4
	mm	188	188
C =	in.	2.7	2.7
	Ø max mm	70	70

## FILTER-REGULATOR-LUBRICATORS

PART #: NPT	PART#: BSP	SIZE	TYPE	MAX. FLOW RATE	
				cfm	l/sec
<b>894 016 8515</b>	<b>894 016 8478</b>	1/4"	2 stage	80	37
<b>894 016 8517</b>	<b>894 016 8480</b>	1/2"	2 stage	110	50

More references available in the CP Maintenance Catalog



FRL units will improve the productivity and life of your CP impact wrench.

## IMPACT SOCKET SETS

PART #:	MODEL #:	DESCRIPTION
<b>Thin wall wheel protector</b>		
<b>894 016 4464</b>	<b>SS413WP</b>	1/2" drive 3PC set sizes 17, 19, 21 mm
<b>894 016 8375</b>	<b>SS414WP</b>	1/2" drive 4PC set sizes 17, 19, 21, 22 mm
<b>894 016 4465</b>	<b>SS4013</b>	1/2" drive 13PC SAE SET
<b>894 016 4458</b>	<b>SS4114</b>	1/2" drive 14PC Metric SET



Impact sockets are laser etched for easy identification. Sets are supplied in a sturdy blow molded case.

## OPERATOR ACCESSORIES

PART #:	DESCRIPTION
<b>Gloves</b>	
<b>894 015 8618</b>	Impact gloves - Large
<b>894 015 8619</b>	Impact gloves - X-Large
<b>Tool holder</b>	
<b>894 016 6664</b>	CP9841 magnetic tool holder



Magnetic tool holder for convenient workstation organization.