

HOFMANN®



geodyna™ 800

WHEEL BALANCER

geodyna™ 800

The geodyna 800 wheel balancer is designed with the quality and durability associated with the Hofmann brand at an affordable price. The bright LED display clearly exhibits wheel weight, while colored sequencing LED's indicate weight location. For specialty balancing, there are five tape weight modes and a static only mode.

Features

- Manual data entry of wheel distance, width and diameter.
- Dynamic two-plane balancing for passenger cars.
- 5 ALU modes.
- Motorcycle mode.
- Gram/Ounce toggle.
- Fine mode.
- Membrane metal buttons for quick, easy and durable balancer accuracy.
- Self-diagnostic program minimizes maintenance.



EEWBUS732A

Wheel Balancer

Specifications

Maximum Wheel & Tire Assembly Weight	143 lbs.
Maximum Tire Diameter	35"
Maximum Wheel Width	20"
Wheel Diameter Range	12" - 22"
Balancer Shaft Diameter	40mm
Measuring Speed	200 RPM
Weight Storage Pockets	9
Data Entry (Wheel Dist., Diam., Width)	Manual
Display	Integrated LED
Dimensions (DxWxH)	44" x 41" x 64"
Shipping Weight	265 lbs.
Power Requirements:	120V, 1Ph, 60Hz

Standard Accessories

EAM0005D23A	Automotive Cone (1.65" - 3.03")
EAM0005D24A	Automotive Cone (2.83" - 3.90")
EAM0005D25A	Automotive Cone (3.78" - 4.57")
EAM0005D40A	Calibration Tool
EAA0263G66A	Quick-Nut
EAC0058D07A	Large Pressure Cup
EAC0058D08A	Small Pressure Disc
EAC0058D15A	Soft Protective Ring
EAM0006G01A	Storage Peg
00058839000	Weight Pliers

Hofmann manufactures a complete line of wheel service equipment.



General-Purpose
Lifts



Tire
Changers



Portable Imaging Alignment
Systems

HOFMANN®

USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca